

Manual/Thermal Activation Stat-X[®] Fire Suppression Generators



Model	Part No.	Aerosol Mass	Shipping Weight	Length	Diameter	Discharge Time
30T	15300	.03 kg. /.07 lb.	.26 kg. /.60 lb.	109 mm/ 4.30 inches	51 mm/ 2.00 inches	8 seconds
60T	15310	.06 kg. /.14 lb.	.35 kg. /.80 lb.	142 mm/ 5.60 inches	51 mm/ 2.00 inches	8.5 Seconds
60T Long	15311	.06 kg. /.14 lb.	.55 kg. /1.23 lbs.	155 mm/ 6.10 inches	51 mm/ 2.00 inches	8.5 seconds
100T	15410	.10 kg. /.22 lb.	1.44 kg. /3.20 lbs.	152 mm/ 6.00 inches	76 mm/ 3.00 inches	11.5 seconds
250T	15510	.25 kg. /.55 lb.	2.72 kgs. /6.00 lbs.	168 mm/ 6.60 inches	127 mm/ 5.00 inches	12 Seconds
250MT	15511	.25 kg. /.55 lb.	1.87 kgs. /4.12 lbs.	202 mm/ 7.95 inches	76 mm/ 3.00 inches	18 seconds
500T	15610	.5 kg. /1.10 lb.	3.63 kgs. /8 lbs.	218 mm/ 8.60 inches	127 mm/ 5.00 inches	21 seconds
1000MT	15711	1 kg. /2.20 lb.	5.6 kgs. /12.40 lbs.	333 mm/ 13.10 inches	127 mm/ 5.00 inches	25 seconds

Please note that the length dimensions and weights that are listed above for the Stat-X generators are based on the length of the generators with the thermal/manual heads installed on the generators. For additional information on use of Stat-X systems, please contact your local distributor or Fireaway Inc.

Operation/Storage Parameters:

Temperature -0° C to +54° C (+32° F to 130°F)
Relative Humidity up to 98% at +35° C (+95° F)

Transportation Classification:

- Classification Code: 4.1
- UN Identification #: UN 3178
- Packaging Group: PGIII
- Shipping Limitations:
 - Ground: None
 - Max. weight per unit packaging - Cargo Air 100 kgs (220 lbs)
 - Max. weight per unit packaging - Passenger Air 25 kgs (55 lbs)



RINA

